

*Fig.1*




Fig.2







Fig.3



*Fig.4*



*Fig.5*



## Welcome to your Power Webench™!

"Tools for the power design engineer"

### **START HERE**

to design a power supply.

## How to Use Webench

Just four easy steps to design a power supply! Just click on the items below for help on that step.

### **1 Choose a Part**

choose a specific part or input your system specifications to find those devices that fit.

### **2 Create a Design**

a design will be created for you including any necessary passive components and important calculated operating values.

### **3 Analyze a Design**

use WebSim™, the online power simulator, to validate your design electrically, and WebTHERM™, the online thermal simulator to visualize the thermal behavior of your design.

### **4 Build It!**

buy a part, a kit of parts, or an evaluation board.

[See Our Disclaimer](#)

## My Designs

### Your last 4 designs:

- [Design#6](#)
- [Design#5](#)
- [Design#4](#)
- [Design#3](#)

[MY Designs Shows all of your Designs](#)

[My WebSIM™ Simulations](#)

[My WebTHERM™ Simulations](#)

[My BuildIt Orders](#)

## Other Power Webench Tools

**Switchers Made Simple™** is downloadable software that enables you to develop a complete power supply design on your local PC. This covers Simple Switcher devices and includes discrete component and manufacturer selection.

- [SMS 6.1](#) (for LM267x and LM259x buck regulators, and LM258x and LM2577 boost & flyback regulators)  
**Updated!**

- [SMS 3.3](#) (for LM257X)


## Wireless Webench Tools

- [Wireless Easy PLL Design Assistant](#)

## Features

**WebSIM™** is a browser-based simulator which allows you to probe points in the

FIG. 6



Enter your power supply design requirements.

### Basic Selections

7902

Vin Min	20	V
Vin Max	22	V

Output Voltage: 5 Volts

Output #1: V out 5.0 V, I out 5 A

704

### Choose Additional features (Optional)


On/Off Pin	<input type="radio"/> No	<input type="radio"/> Yes	<input checked="" type="radio"/> Ignore
Error Flag	<input type="radio"/> No	<input type="radio"/> Yes	<input checked="" type="radio"/> Ignore
Sync Pin	<input type="radio"/> No	<input type="radio"/> Yes	<input checked="" type="radio"/> Ignore

Output 2: V out, I out


Output 3: V out, I out

706

Show Recommended Power Management ICs




F16. 7



① Choose a Part

Help



### Your Design Specifications

VinMin: 20.0V	<b>Output #1</b>
VinMax: 22.0V	Vout= 5.0V
	Iout= 5.0A

### Suggested Switching Regulators - Buck Topology

Product Folder	Webench Tools	Max Curr.	Typ. Eff.	On/Off	Err. Pin	Other Features	Freq. kHz	Est. Price
LM2678-5.0	Create Design WebTHERM™ enabled Build It - Custom Kit	5.0A 806	84%	Y	Y		260	\$3.84
LM2678-ADJ	Create Design WebTHERM™ enabled Build It - Custom Kit	5.0A 800	84%	Y	Y	Adj. Vout	260	\$3.84
LM2679-5.0	Create Design WebTHERM™ enabled Build It - Custom Kit	5.0A 806	84%	Y	Y	SoftStart, Adj. Peak Current Limit	260	\$4.07
LM2679-ADJ	Create Design WebTHERM™ enabled Build It - Custom Kit	5.0A 806	84%	Y	Y	SoftStart, Adj. Peak Current Limit, Adj. Vout	260	\$4.07

### Suggested Switching Regulators - Flyback Topology


Product Folder	Webench Tools	Max Curr.	Typ. Eff.	On/Off	Err. Pin	Other Features	Freq. kHz	Est. Price
LM2585-5.0	Create Design	3.0A	93%	N	N	SoftStart	100	\$3.42
LM2585-ADJ	Create Design	3.0A	80%	N	N	SoftStart, Adj. Vout	100	\$3.42
LM2586-5.0	Create Design	3.0A	80%	Y	N	Sync, SoftStart	100	\$3.45
LM2586-ADJ	Create Design	3.0A	80%	Y	N	Sync, SoftStart, Adj. Vout	100	\$3.45
LM2587-5.0	Create Design	5.0A	80%	N	N	SoftStart	100	\$4.51
LM2587-ADJ	Create Design	5.0A	80%	N	N	SoftStart, Adj. Vout	100	\$4.51
LM2588-5.0	Create Design	5.0A	80%	Y	N	Sync, SoftStart	100	\$4.61
LM2588-ADJ	Create Design	5.0A	80%	Y	N	Sync, SoftStart, Adj. Vout	100	\$4.61
LM2577-ADJ	Create Design	3.0A	80%	N	N	SoftStart, Adj. Vout	52	\$3.15

FIG. 8





Design • Purchasing • Quality • Company • Jobs



Products > Analog - Regulators > Simple Switchers > LM2679

Product Folder

Live Simulation

Buy LM2679-5.0 Evaluation Board

## LM2679 SIMPLE SWITCHER 5A Step-Down Voltage Regulator with Adjustable Current Limit


Generic P/N 2679

### Contents

- [General Description](#)
- [Features](#)
- [Applications](#)
- [Datasheet](#)
- [Package Availability, Models, Samples & Pricing](#)
- [Design Tools](#)

Parametric Table	
Multiple Output Capability	No
On/Off Pin	Yes
Error Flag	Yes
Input Voltage, min (Volt)	8,15
Input Voltage, max (Volt)	40
Output Current, max	5 Amps
Output Voltage (Volt)	5,12,3.30
Adjustable Output Voltage	No,Yes
Switching Frequency (Hz)	260000
Adjustable Switching Frequency	No
Sync Pin	No
Efficiency (%)	84,92,82
Flyback	No
Step-up	No
Step-down	Yes

FIG. 9

 **MY WEBENCH™**

**1 Choose a Part** **2 Create a Design** **3 Analyze a Design** **4 Build It!** [Help](#)






[Components](#) [Operating Values](#) [Schematic](#) [MY Designs](#)

Design: Design#7  
Device: LM2679 Mar 17 2001 3:39PM ID: 266796\_7


**Design Requirements** Output #1  
VinMin = 20.00 V Vout= 5.00 V  
VinMax = 22.00 V Iout= 5.00 A

[Choose Operation](#)  
[Copy](#)  
[Rename, Add Notes](#)  
[Print, XML](#)  
[Share this Design](#)

**Webtherm - Thermal Simulation** **Websim - Electrical Simulation**

Components					
Part	Manufacturer	Part#	Attributes	Thermally Modelled*	
Cb	Vishay-Vitramon	VJ1206Y103KXAAT	0.0100 uF	Y	Select Alternate Part
Cin	Vishay-Sprague	594D156X0035D2T	NumCaps=3 15.000 uF,0.2650 Ohms		Select Alternate Part
Cout	Vishay-Sprague	594D187X0016R2T	NumCaps=1 180.00 uF,0.0650 Ohms		Select Alternate Part
Css	Vishay-Vitramon	VJ1206A392JXAAT	0.0039 uF	Y	Select Alternate Part
D1	International Rectifier	6CWQ03FN	0.450000 V		Select Alternate Part
IC	National Semiconductor	LM2679S-ADJ	ADJV,Buck		Select Alternate Part
L1	Coiltronics	UP4B-150	15.000 uH,0.0200 Ohms		Select Alternate Part
Rfb1	Vishay-Dale	CRCW1206-1001FRT1	1000 Ohms	Y	Select Alternate Part
Rfb2	Vishay-Dale	CRCW1206-3161FRT1	3160 Ohms	Y	Select Alternate Part
Rlim	Vishay-Dale	CRCW1206-4991FRT1	4990 Ohms	Y	Select Alternate Part

\*Components marked "Y" are not required for Thermal Simulation.





Select Alternate for Component D1

Please select from the list of available alternates below. Click on the "Update BOM" button when you are done.

Alternates	Part #	Manufacturer	Thermally Modelled	Forward Voltage Drop	Max Rated Current	Max Voltage Rating	X,Y,Z in mm	Price	Quantity Available
Custom <input type="radio"/>			N	Limit = 0.00 V	Limit >= 5.00 A	Limit >= 26.4 V	1112		
1 <input type="radio"/>	6CWQ03FN	International Rectifier		0.45000 V	7.000 A	30.00 V	10.42 6.73 2.38	\$0.85	>10 in stock
2 <input type="radio"/>	50WQ03FN	International Rectifier		0.46000 V	5.500 A	30.00 V	10.42 6.73 2.38	\$1.83	>10 in stock
3 <input type="radio"/>	12CWQ03FNTRL	International Rectifier		0.47000 V	12.00 A	30.00 V	10.42 6.73 2.38	\$0.82	>10 in stock
4 <input type="radio"/>	50WQ04FN	International Rectifier		0.51000 V	5.500 A	40.00 V	10.42 6.73 2.38	\$1.33	>10 in stock
5 <input checked="" type="radio"/>	12CWQ04FN	International Rectifier		0.52000 V	12.00 A	40.00 V	10.42 6.73 2.38	\$1.48	>10 in stock
6 <input type="radio"/>	6CWQ04FN	International Rectifier		0.53000 V	7.000 A	40.00 V	10.42 6.73 2.38	\$1.00	>10 in stock
7 <input type="radio"/>	50WQ06FN	International Rectifier		0.57000 V	5.500 A	60.00 V	10.42 6.73 2.38	\$1.07	>10 in stock
8 <input type="radio"/>	12CWQ06FN	International Rectifier		0.61000 V	12.00 A	60.00 V	10.42 6.73 2.38	\$0.72	>10 in stock
9 <input type="radio"/>	6CWQ06FNTR	International Rectifier		0.61000 V	7.000 A	60.00 V	10.42 6.73 2.38	\$1.08	>10 in stock

Update BOM

FIG. 11

 **WEBENCH™**  **Online Support**

**1 Choose a Part** **2 Create a Design** **3 Analyze a Design** **4 Build It!** [Help](#)

**Components** **Operating Values** **Schematic** **MY Designs**

Design: Design#7			<b>Choose Operation</b> <a href="#">Copy</a> <a href="#">Rename</a> , <a href="#">Add Notes</a> <a href="#">Print XML</a> <a href="#">Share this Design</a>
Device: LM2679	Mar 17 2001 3:39:00:000PM	ID: 266796_7	
<b>Design Requirements</b>	Output #1		
VinMin = 20.00 V	Vout= 5.00 V		
VinMax = 22.00 V	Iout= 5.00 A		

Vin:  V Iout:  A


Operating Values			
#	Description	Parameter	Value
1	Pulse Width Modulation (PWM) frequency	Frequency	260 kHz
2	Continuous or Discontinuous Conduction mode, inductor current goes to zero in Discontinuous Conduction	Mode	Cont
3	Total Output Power	Pout	25.0 W
4	Vin operating point	Vin Op	22.00 V
5	Iout operating point	Iout Op	5.00 A

Operating Point at Vin= 22.00 V,5.00 A			
#	Description	Parameter	Value
1	Bode Plot Crossover Frequency, indication of bandwidth of supply	Cross Freq	97.7 kHz
2	Steady State PWM Duty Cycle, range limits from 0 to 100	Duty Cycle	25.8 %
3	Steady State Efficiency	Efficiency	85.3 %
4	IC Junction Temperature	IC Tj	120 °C
5	IC Junction to Ambient Thermal Resistance	ICThetaJA	34.9 °C/W
6	Bode Plot Phase Margin	Phase Marg	71.0 Deg
7	Peak-to-peak ripple voltage	Vout p-p	0.07 V

FIG. 12A

Current Analysis			
#	Description	Parameter	Value
1	Input Capacitor RMS ripple current	Cin IRMS	2.2 A
2	Output Capacitor RMS ripple current	Cout IRMS	0.20 A
3	Peak Current in IC for Steady State Operating Point	IC Ipk	5.5 A
4	ICs Maximum rated peak current	IC Ipk Max	7.4 A
5	Average input current	Iin Avg	2.3 A
6	Inductor ripple current, peak-to-peak value	L Ipp	1.1 A

Power Dissipation Analysis			
#	Description	Parameter	Value
1	Input Capacitor Power Dissipation	Cin Pd	0.43 W
2	Output Capacitor Power Dissipation	Cout Pd	0.0026 W
3	Diode Power Dissipation	Diode Pd	1.9 W
4	IC Power Dissipation	IC Pd	1.4 W
5	Inductor Power Dissipation	L Pd	0.50 W



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is QS 9000 Certified  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . **MY:** [Preferences](#) . [Feedback](#)

FIG. 12B





FIG. 13



### WebTHERM™ Simulations :

#### Simulation

ID	Name	Status	Date	Comments
	(click to view)			

No WebTHERM™ simulation info.

Click [here](#) to see a list of all of your WebTHERM Simulations.

Please click [Refresh](#) to get updated status of your simulations.

We will also send you email notification when your simulations are complete. It will contain a URL which can be clicked for viewing your simulations.

Queued time is dependent on the number of requests in the queue.

Processing time for each simulation is estimated about 2-3 minutes.





Fig. 14



Design: Design#7

Device: LM2679

Mar 17 2001 3:39:00:000PM

ID: 266796\_7

### Design Requirements

Output #1

VinMin = 20.00 V

Vout= 5.00 V

VinMax = 22.00 V

Iout= 5.00 A

WebTHERM™

Powered by: **FLUENT**

When you have entered all your data, click here:

[SUBMIT for new simulation](#)

Simulation ID : 4

Name This Simulation:

Simulation for Design 7

Comments:

Environment:

Operating Conditions

Vin: 22.00 V Iout: 5.00 A

Ambient Temperature  
On Bottom: 30 °C On Top: 30 °C

Board Conditions

Copper Weight

1 OZ. (0.03556 mm)

Board Orientation:

Component Side Up

Air Flow

Direction:

Velocity:

Edge Temperatures:

Edge 1

☒ Insulated OR

N/A °C

Edge 4

☒ Insulated

OR  
N/A °C

Edge 2

☒ Insulated

OR  
N/A °C

Edge 3

☒ Insulated OR

N/A °C





Fig. 15A





BOM			
Component	Power Dissipation	Manufacturer	Part#
Cin	0.43 W	Vishay-Sprague	594D156X0035D2T
Cout	0.0026 W	Vishay-Sprague	594D187X0016R2T
D1	1.9 W	International Rectifier	12CWQ04FN
IC	1.4 W	National Semiconductor	LM2679
L1	0.50 W	Coiltronics	UP4B-150


### Design Assistant Messages

All components fit!



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is QS 9000 Certified  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . **MY:** [Preferences](#) . [Feedback](#)

FIG. 15B



### WebTHERM™ Simulations :


ID	Name	Status	Date	Comments
(click to view)				
7 = Design ID	Simulations for Design ID : 7			Design ID : 7
1	Simulation for Design 7	queued	Mar 17 2001 5:05:45 PM	

Please click **Refresh** to get updated status of your simulations.

We will also send you email notification when your simulations are complete. It will contain a URL which can be clicked for viewing your simulations.


Queued time is dependent on the number of requests in the queue.

Processing time for each simulation is estimated about 2-3 minutes.



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is [QS 9000 Certified](#)  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig. 16



### WebTHERM™ Simulations :


Simulation		Status	Date	Comments	
ID	Name				
(click to view)					
7 =	Design ID	Simulations for Design ID : 7		Design ID : 7	
1	Simulation for Design 7	processing	Mar 17 2001 5:05:57 PM		

**Please click Refresh to get updated status of your simulations.**

We will also send you email notification when your simulations are complete. It will contain a URL which can be clicked for viewing your simulations.


Queued time is dependent on the number of requests in the queue.

Processing time for each simulation is estimated about 2-3 minutes.



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is [QS 9000 Certified](#)  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig. 17



#### WebTHERM™ Simulations :


Simulation				
ID	Name	Status	Date	Comments
(click to view)				
7 = Design ID		Simulations for Design ID : 7		Design ID : 7
<u>1</u>	<u>Simulation for Design 7</u>	<u>completed</u>	Mar 17 2001 5:10:22 PM	

**Please click Refresh to get updated status of your simulations.**

We will also send you email notification when your simulations are complete. It will contain a URL which can be clicked for viewing your simulations.


Queued time is dependent on the number of requests in the queue.

Processing time for each simulation is estimated about 2-3 minutes.



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is QS 9000 Certified  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig. 18



Design: Design#7

Device: LM2679

Mar 17 2001 3:39:00:000PM

ID: 266796\_7

### Design Requirements

Output #1

VinMin = 20.00 V

Vout= 5.00 V

VinMax = 22.00 V

Iout= 5.00 A

Powered by:  
**WebTHERM™ FLOMERICS**

[Download Flomerics SMARTPART™ model](#)

[Do another simulation](#)

Simulation ID : 1  
Name This  
Simulation:  
Simulation for  
Design 7

### Edge Temperatures:

Edge 1  
Insulated

### Environment:

#### Operating Conditions


Vin: 22.00 V

Iout: 5.00 A

Ambient Temperature  
On On Top:  
Bottom: 30 °C  
30 °C

Board Conditions  
Copper Weight  
0.5 OZ. (0.01778 mm)  
Board Orientation:  
Component Side Up

Air Flow  
Direction Velocity:  
of Air  
flow: No Fan



Temperature Bar Scaling  
Click [here](#) to recolor your thermal image.

Max Colorbar Temperature

188 °C

Min Colorbar Temperature

46 °C


FIG. 19A

~2030

Operating Temperatures				
Layer	Max Temp.	Manufacturer	Part#	Warnings
Cin	82°C	Vishay-Sprague	594D156X0035D2T	
Cout	92°C	Vishay-Sprague	594D187X0016R2T	
D1 - Diode	188°C	International Rectifier	12CWQ04FN	
IC - Die	174°C	National Semiconductor	LM2679	There is some potential problem with this design.
IC - Top	165°C			
L1 - Inductor	82°C	Coiltronics	UP4B-150	
PCB	182°C			


### Design Assistant Messages

All components fit!



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is [QS 9000 Certified](#)  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . **MY:** [Preferences](#) . [Feedback](#)

FIG. 19B



Design: Design#7

Device: LM2679

Mar 17 2001 3:39:00:000PM ID: 266796\_7

### Design Requirements

Output #1

VinMin = 20.00 V Vout= 5.00 V

VinMax = 22.00 V Iout= 5.00 A

Powered by:  
**WebTHERM™ FLOMERICS**

[Download Flomerics SMARTPART™ model](#)

[Do another simulation](#)

**Simulation ID : 3**  
**Name This Simulation:**  
Simulation for Design 7

**Edge Temperatures:**  
Edge 1  
Insulated


### Environment:

**Operating Conditions**  
Vin: 22.00 V  
Iout: 5.00 A


**Ambient Temperature**  
On Bottom: 30 °C  
On Top: 30 °C

**Board Conditions**  
**Copper Weight**  
0.5 OZ. (0.01778 mm)  
**Board Orientation:**  
Component Side Up

**Air Flow**  
**Direction Velocity:**  
of Air  
flow: 400 LFM



Edge 4  
Insulated



Edge 3  
Insulated

Edge 2  
Insulated

**Temperature Bar Scaling**  
[Click here to recolor your thermal image.](#)


Max Colorbar Temperature 128 °C  
Min Colorbar Temperature 32 °C

FIG. 20A

Operating Temperatures				
Layer	Max Temp.	Manufacturer	Part#	Warnings
Cin	50°C	Vishay-Sprague	594D156X0035D2T	
Cout	50°C	Vishay-Sprague	594D187X0016R2T	
D1 - Diode	128°C	International Rectifier	12CWQ04FN	
IC - Die	112°C	National Semiconductor	LM2679	There is some potential problem with this design.
IC - Top	97°C			
L1 - Inductor	46°C	Coiltronics	UP4B-150	
PCB	123°C			

### Design Assistant Messages


All components fit!



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is [QS 9000 Certified](#)  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

FIG 20B





Design : 7

2210

Your design is supported by a Webench Custom Evaluation Kit. Ordering this kit from Pioneer-Standard provides you with everything you need to realize a prototype of your design quickly and at a very low price.

If for some reason you decide not to order the Custom Evaluation Kit you can always order only the IC from us here.

## Custom Evaluation Kit

2210





2230

## Bill of Materials

[View Assembly Doc](#) | [Order this Kit from Pioneer-Standard >>](#)

Item	Manufacturer Part	Qty	Attributes	Component Name(s)	Pioneer Price	Pioneer Availability
1	International Rectifier 12CWQ04FN	1	V <sub>Fatlo</sub> = 0.52 V	D1	\$1.48	> 10 In Stock
2	Keystone 5015	4		TP1, TP2, TP3, TP6	\$0.20	> 10 In Stock
3	National Semiconductor 551011367-011	1	Surface Mount, etc	PC Board	\$5.00	> 10 In Stock
4	Vishay-Sprague 594D156X0035D2T	3	Cap = 15uF ESR = 0.265 Ohms	Cin	\$1.00	> 10 In Stock
5	Vishay-Sprague 594D187X0016R2T	1	Cap = 180uF ESR = 0.065 Ohms	Cout	\$1.00	> 10 In Stock
6	Vishay-Dale CRCW1206-1001FRT1	1	Resistance = 1000 Ohms	Rfb1	\$0.03	> 10 In Stock
7	Vishay-Dale CRCW1206-3161FRT1	1	Resistance = 3160 Ohms	Rfb2	\$0.03	> 10 In Stock
8	Vishay-Dale CRCW1206-4991FRT1	1	Resistance = 4990 Ohms	Rilim	\$0.03	> 10 In Stock
9	National Semiconductor LM2679S-ADJ	1	Package=S, Voltage option=ADJ, Topology=Buck	IC	\$4.75	> 10 In Stock

Fig. 21A

10	 Coiltronics UP4B-150	1	L = 15uH DCR = 0.02 Ohms	L1	\$1.50	> 10 In Stock
11	 Vishay-Vitramon VJ1206A392JXAAT	1	Cap = 0.0039uF	Css	\$0.05	> 10 In Stock
12	 Vishay-Vitramon VJ1206Y103KXAAT	1	Cap = 0.01uF	Cb	\$0.05	> 10 In Stock
13	 Vishay-Vitramon VJ1206Y104KXAAT	1		Cinx	\$0.05	> 10 In Stock
Total					\$17.77	

## Bill of Materials

[View Assembly Doc](#) [Order this Kit from Pioneer-Standard >>](#)

## Order the IC


- [Order the LM2679S-ADJ in volume.](#)
- [Order a Free Sample](#)

## Generic Eval Board for LM2679

- [Buy Eval Board for LM2679](#)
- [Download Protel File \(See Notes below\)](#)


The Protel files are saved as Self Extracting Zip Archives. To download a product's Protel file, click on the corresponding "Protel file now" link, and save the link as a file on your computer. Then run the file on your computer (double click). This will automatically decompress the Protel file to your computer's disk.

**Note:** You must have Protel software or other software that can read Protel PCB layout files in order to take advantage of these Protel files.




[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is QS 9000 Certified  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig 213



**Assembly Document for Your LM2679 Design # : 7**  
**LM2679 SMD Evaluation Board (LM2679BU1PWB)**



**FIGURE 1 - Assembly Diagram**

**Download the Board Layout in Protel format.**














**GENERAL DESCRIPTION**

*Fig. 22A*

The LM2679 SMD Evaluation Board is designed to provide a flexible PCB platform for customers to develop and test custom power supply designs using tools available on the POWER.NATIONAL.COM website. The LM2679BU1PWB is a single sided surface mount layout using 1oz copper. The overall board dimensions are 2.475" x 2.700" All components are mounted on the topside copper. WEBENCH™ has automatically placed the components on this board to make sure that the input capacitor Cin (and Cinx) and the diode D1 are as close to the IC as is reasonable minimizing stray circuit inductance. L1 and Cout should also be as close to the IC as is reasonable but mostly to minimize the overall dimensions of the required PCB area for the power supply.

The LM2679 SMD Evaluation Board consists of a single layer PCB layout providing major landing areas on the PCB for the Power conversion components: Inductor, Diode, Input and Output Capacitors as well as parameter setting small signal passive (resistors and capacitors) in 1206 packages and surface mount test points. Some components are optional or specific to an application, these are highlighted in the schematic. The PCB layout can be optimized for a specific design and lends itself to be dimensionally scalable (i.e. your particular design may have unused board area that can be "cut out" in the final application. This topic is covered in the PCB Layout Optimization section.

### Bill of Materials (BOM).

Item	Manufacturer Part	Qty	Attributes	Component Name(s)
1	International Rectifier 12CWQ04FN 	1	V <sub>F</sub> at <sub>10</sub> = 0.52 V	D1
2	Keystone 5015 	4		TP1, TP2, TP3, TP6
3	National Semiconductor 551011367-011 	1	Surface Mount, etc	PC Board
4	Vishay-Sprague 594D156X0035D2T 	3	Cap = 15uF ESR = 0.265 Ohms	Cin
5	Vishay-Sprague 594D187X0016R2T 	1	Cap = 180uF ESR = 0.065 Ohms	Cout
6	Vishay-Dale CRCW1206-1001FRT1 	1	Resistance = 1000 Ohms	Rfb1
7	Vishay-Dale CRCW1206-3161FRT1 	1	Resistance = 3160 Ohms	Rfb2
8	Vishay-Dale CRCW1206-4991FRT1 	1	Resistance = 4990 Ohms	Rilim
9	National Semiconductor LM2679S-ADJ 	1	Package=S, Voltage option=ADJ, Topology=Buck	IC
10	Coiltronics UP4B-150 	1	L = 15uH DCR = 0.02 Ohms	L1
11	Vishay-Vitramon VJ1206A392JXAAT 	1	Cap = 0.0039uF	Css
12	Vishay-Vitramon VJ1206Y103KXAAT 	1	Cap = 0.01uF	Cb
13	Vishay-Vitramon VJ1206Y104KXAAT 	1		Cinx

770-223

## SCHEMATIC

The schematic for the LM2679 is shown in FIGURE 2. U1, L1, D1, Cin and Cout are the basic power conversion components. Cinx as a high frequency bypass to the input to the LM2679. Rf1, Rfb2, and Cf form the feedback network for the adjustable version of the LM2679. For Fixed output versions a zero Ohm resistor (jumper) should be used for Rfb2 (Rfb1 and Cf should be left off the board), this can be replaced by a copper trace as shown in the PCB Layout Optimization section. A space is reserved for a pull-down resistor, Ron, for the ON/OFF (Active low) pin, this may be desired if a Tri-State gate is driving this pin. Otherwise, if the ON/OFF pin is left floating, the LM2679 is normally ON.




FIGURE 2. - Schematic

[Download the Schematic file in Protel format.](#)

## Component Testing

Some published data on components in datasheets such as Capacitor ESR and Inductor DC resistance is based on conservative values that will guarantee that the components always exceed the specification. For design purposes it is usually better to work with typical values. Since this data is not always available it is a good practice to measure the Capacitance and ESR values of Cin and Cout, and the inductance and DC resistance of L1 before assembly of the board. Any large discrepancies in values should be electrically simulated to check for instabilities and thermally simulated to make sure critical temperatures are not exceeded.

## Soldering components to the Board

If board assembly is done in house it is best to tack down one terminal on the board then solder the other terminal. For the LM2679 the tab on the back of the TO-263 package should be pre-tinned with solder, then tacked into place by one of the pins. To solder the tab down to the board place the iron down on the board while resting against the tab, heating both surfaces simultaneously. Apply light pressure to the top of the plastic case until the solder flows around the part and the part is flush with the PCB. If the solder is not flowing around the board you may need a higher wattage iron (generally 25W to 30W is enough).

## Testing

It is best to power up the board by setting the supply voltage to the lowest operating input voltage (Vin min) and set the supplies current limit to zero. With the supply off connect up the supply to Vin and GND. Connect a DVM to Vout and GND. Turn on the supply and slowly turn up the current limit. If the voltage starts to rise on the supply continue increasing the current while watching the output voltage. If the current increases on the supply but the voltage remains near zero there may be a short or a component misplaced on the board. Power down the board and visually inspect for solder bridges and recheck the diode and capacitor polarities. Once the supply is operational then more extensive testing may include full load testing, transient load and line tests to compare with simulation results.

Fig 22C


## ARTWORK

FIGURE 3 shows the topside copper and FIGURE 4 shows the bottom side copper.

The intent of the this board is to provide a flexible PCB layout to allow many different designs to be implemented using the same layout. In lower power designs you may find unused board space, that is not needed for electrical or thermal purposes. The overall layout lends itself to shrinking the design by trimming off the outer edges of the board.

**Download the GERBER file for this PC Board.**


- NOTES: UNLESS OTHERWISE SPECIFIED
1. NO FAB SHOP LOGO<DATE CODE REQUIRED>
  2. APPLY GREEN (LPI) SOLDERMASK ON BOTH SIDES
  3. NO SILKSCREEN
  4. ADD UL RATING ON BOTTOM SIDE
  5. MATERIAL: FR-4, GREEN
  6. BOARD THICKNESS: 0.063 with 1 oz Copper
  7. FINISH: TIN-LEAD



**FIGURE 3 - Topside Copper**

- NOTES: UNLESS OTHERWISE SPECIFIED
1. NO FAB SHOP LOGO<DATE CODE REQUIRED>
  2. APPLY GREEN (LPI) SOLDERMASK ON BOTH SIDES
  3. NO SILKSCREEN
  4. ADD UL RATING ON BOTTOM SIDE
  5. MATERIAL: FR-4, GREEN
  6. BOARD THICKNESS: 0.063 with 1 oz Copper
  7. FINISH: TIN-LEAD

Fig 220 +



**FIGURE 4 - Bottom Side Copper**

## Downloadable files

## Schematic File


**The Schematic File in Protel format.**

## **Board Layout File**

**Board Layout in Protel format.**


## GERBER File

GERBER file for making the PC Board.



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . [National is QS 9000 Certified](#)  
[Site Terms & Conditions of Use](#) . [Copyright 2001 © National Semiconductor Corporation](#)  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig 22E



Design : 6

## WEBENCH Documentation

### Assembly Doc.

The Webench Assembly Document describes in detail how to build your design. It contains the specific assembly diagram for your design, a complete bill of materials and other PC board images and assembly instructions.

### Design Doc.

The WEBENCH Design Document provides a single web page describing your entire design including; design specifications, calculated values, WebSIM simulation results and WebTHERM simulation results.

### LM2679 Folder

LM2679 Product Folder is full of documentation about the National IC used in your design.

### My Orders

My Orders is a list of all of your on-line orders.

## WEBENCH Downloads

You can download these files to integrate this design into your local CAD environment. These file are self-extracting zip files. For the files stored in Protel format you will need the Protel application or equivalent CAD software capable of opening such files.

### Schematic File


The Schematic File in Protel format.

### Board Layout File

Board Layout in Protel format.

### GERBER File


GERBER file for making the PC Board.



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is QS 9000 Certified  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig. 23





## Design Document for Your LM2679 Design # : 7

### Table of Contents

1. Introduction
2. Design Specifications
3. Schematic
4. Operating Values
5. The Selected IC
6. BOM - Bill of Materials
7. WebTHERM Results
8. Build It!
9. Appendices

### Introduction

Custom power supply designs using tools are available on the [POWER.NATIONAL.COM](http://POWER.NATIONAL.COM) website.

### Design Specifications

Design: Design#7

Device: LM2679

Mar 17 2001 3:39PM

ID: 266796\_7

#### Design Requirements

VinMin = 20.00 V

Output #1  
Vout= 5.00 V

VinMax = 22.00 V

Iout= 5.00 A

### Schematic

Use [WebSIM](#) to display your schematic.

### Operating Values

Fig 24A

Operating Values			
#	Description	Parameter	Value
1	Pulse Width Modulation (PWM) frequency	Frequency	260 kHz
2	Continuous or Discontinuous Conduction mode, inductor current goes to zero in Discontinuous Conduction	Mode	Cont
3	Total Output Power	Pout	25.0 W

Operating Point at Vin= 22.00 V			
#	Description	Parameter	Value
1	Bode Plot Crossover Frequency, indication of bandwidth of supply	Cross Freq	97.7 kHz
2	Steady State PWM Duty Cycle, range limits from 0 to 100	Duty Cycle	25.8 %
3	Steady State Efficiency	Efficiency	85.3 %
4	IC Junction Temperature	IC Tj	120 °C
5	IC Junction to Ambient Thermal Resistance	ICThetaJA	34.9 °C/W
6	Bode Plot Phase Margin	Phase Marg	71.0 Deg
7	Peak-to-peak ripple voltage	Vout p-p	0.07 V

Current Analysis			
#	Description	Parameter	Value
1	Input Capacitor RMS ripple current	Cin IRMS	2.2 A
2	Output Capacitor RMS ripple current	Cout IRMS	0.20 A
3	Peak Current in IC for Steady State Operating Point	IC Ipk	5.5 A
4	ICs Maximum rated peak current	IC Ipk Max	7.4 A
5	Average input current	Iin Avg	2.3 A
6	Inductor ripple current, peak-to-peak value	L Ipp	1.1 A

Power Dissipation Analysis			
#	Description	Parameter	Value
1	Input Capacitor Power Dissipation	Cin Pd	0.43 W
2	Output Capacitor Power Dissipation	Cout Pd	0.0026 W
3	Diode Power Dissipation	Diode Pd	1.9 W
4	IC Power Dissipation	IC Pd	1.4 W
5	Inductor Power Dissipation	L Pd	0.50 W

## LM2679 The Selected IC

NSID = LM2679S-ADJ

Topology = Buck

Package = S

## BOM - Bill of Materials











Item	Manufacturer Part	Qty	Attributes	Component Name(s)
1	International Rectifier 12CWQ04FN 	1	VFatlo = 0.52 V	D1
2	Keystone 5015	4		TP1, TP2, TP3, TP6

Fig. 24B

3	National Semiconductor 551011367-011	1	Surface Mount, etc	PC Board
4	Vishay-Sprague 594D156X0035D2T 	3	Cap = 15uF ESR = 0.265 Ohms	Cin
5	Vishay-Sprague 594D187X0016R2T 	1	Cap = 180uF ESR = 0.065 Ohms	Cout
6	Vishay-Dale CRCW1206-1001FRT1 	1	Resistance = 1000 Ohms	Rfb1
7	Vishay-Dale CRCW1206-3161FRT1 	1	Resistance = 3160 Ohms	Rfb2
8	Vishay-Dale CRCW1206-4991FRT1 	1	Resistance = 4990 Ohms	Rlim
9	National Semiconductor LM2679S-ADJ	1	Package=S, Voltage option=ADJ, Topology=Buck	IC
10	Coiltronics UP4B-150 	1	L = 15uH DCR = 0.02 Ohms	L1
11	Vishay-Vitramon VJ1206A392JXAAT 	1	Cap = 0.0039uF	Css
12	Vishay-Vitramon VJ1206Y103KXAAT 	1	Cap = 0.01uF	Cb
13	Vishay-Vitramon VJ1206Y104KXAAT 	1		Cinx

## WebTHERM - Thermal Simulation Results

You have performed 3 WebTHERM thermal simulation(s) on this design.  
Here are the results of the most recent one.




Fig. 24C

Be sure to electrically simulate this design using WebSIM.

---

## Build It!

Webench provides both custom and generic evaluation boards to assist you in the building of prototypes of your design. Additionally, for some designs, it is possible to order the complete BOM (Bill of Materials) on-line using Webench.

**A custom evaluation board is available for your design!**

**Webench provides a custom evaluation board which may be on-line ordered from Pioneer-Standard for designs like yours using National LM2679S-ADJ configured in the Buck topology.**


---

## Appendices

**A. You have performed 3 thermal simulation(s) on this design.**


ID	Simulation Name	Date
1	<u>Simulation for Design</u> Z	Mar 17 2001 5:10 PM
2	<u>Simulation for Design</u> Z	Mar 17 2001 5:19 PM
3	<u>Simulation for Design</u> Z	Mar 17 2001 5:23 PM

**B. No electrical simulation(s) performed on this design.**



[About Languages](#) . [Website Guide](#) . [About "Cookies"](#) . National is [QS 9000 Certified](#)  
[Site Terms & Conditions of Use](#) . Copyright 2001 © National Semiconductor Corporation  
[Privacy/Security Statement](#) . [MY: Preferences](#) . [Feedback](#)

Fig. 24D



[Webench™  
Designs]

[WebTHERM™  
Simulations]

[WebSIM™  
Simulations]

[BuildIt  
Orders]

**Tim Sullivan - You have 7 designs stored in your personal workspace.**

ID	Design Name	Device	Creation Date	Modification Date	Design Assistant	Comments	Design Operations
7	<a href="#">Design#7</a>	LM2679	Mar 17 2001 3:39PM	Mar 17 2001 3:57PM	power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>
6	<a href="#">Design#6</a>	LM2679	Mar 15 2001 3:23PM	Mar 15 2001 3:23PM	power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>
5	<a href="#">Design#5</a>	LM2679	Mar 15 2001 11:41AM	Mar 15 2001 11:44AM	power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>
4	<a href="#">Design#4</a>	LM2679	Mar 13 2001 9:52AM	Mar 13 2001 10:03AM	power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>
3	<a href="#">Design#3</a>	LM2679	Mar 13 2001 9:52AM		power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>
2	<a href="#">Design#2</a>	LM2678	Mar 13 2001 9:50AM		power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>
1	<a href="#">Design#1</a>	LM2678	Mar 13 2001 9:50AM		power		<a href="#">Modify</a> , <a href="#">Analyze</a> , <a href="#">Build</a> , <a href="#">Add Notes</a> , <a href="#">Delete</a> , <a href="#">Share</a>

[Quick Search](#)

[Parametric Search](#)

[See Our Disclaimer](#)

[Product Tree](#)

[Back To Webench](#)

Fig. 25